



DC COMPONENTS CO., LTD.

RECTIFIER SPECIALISTS

HBL4A  
THRU  
HBL4M

TECHNICAL SPECIFICATIONS OF SINGLE-PHASE SILICON BRIDGE RECTIFIER  
VOLTAGE RANGE - 50 to 1000 Volts  
CURRENT - 4.0 Amperes

FEATURES

- \* Ideal for printed circuit board
- \* Surge overload rating: 120 Amperes peak

MECHANICAL DATA


- \* Case: Molded plastic
- \* Epoxy: UL 94V-0 rate flame retardant
- \* Terminals: MIL-STD-202E, Method 208 guaranteed
- \* Polarity: Symbols molded or marked on body
- \* Mounting position: Any

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.  
Single phase, half wave, 60Hz, resistive or inductive load.  
For capacitive load, derate current by 20%.



HBL



Dimensions in inches and (millimeters)

	SYMBOL	HBL4A	HBL4B	HBL4D	HBL4G	HBL4J	HBL4K	HBL4M	UNITS	
Maximum Recurrent Peak Reverse Voltage	V <sub>RRM</sub>	50	100	200	400	600	800	1000	Volts	
Maximum RMS Bridge Input Voltage	V <sub>RMS</sub>	35	70	140	280	420	560	700	Volts	
Maximum DC Blocking Voltage	V <sub>DC</sub>	50	100	200	400	600	800	1000	Volts	
Maximum Average Forward Output Current at T <sub>A</sub> = 50°C	I <sub>O</sub>	4.0							Amps	
Peak Forward Surge Current 8.3 ms single half sine-wave superimposed on rated load (JEDEC Method)	I <sub>FSM</sub>	120							Amps	
Maximum Forward Voltage Drop per element at 3.0A DC	V <sub>F</sub>	1.0							Volts	
Maximum DC Reverse Current at Rated DC Blocking Voltage per element	I <sub>R</sub>	@T <sub>A</sub> = 25°C	10							μAmps
		@T <sub>A</sub> = 100°C	500							
I <sup>2</sup> t Rating for Fusing (t*8.3ms)	I <sup>2</sup> t	93							A <sup>2</sup> Sec	
Typical Junction Capacitance ( Note1)	C <sub>J</sub>	40							pF	
Typical Thermal Resistance (Note 2)	R <sub>θJA</sub>	19							°C/W	
Operating Temperature Range	T <sub>J</sub>	-55 to +150							°C	
Storage Temperature Range	T <sub>STG</sub>	-55 to +150							°C	

NOTES : 1. Measured at 1 MHz and applied reverse voltage of 4.0 volts

2. Thermal Resistance from Junction to Case per element Unit mounted on 300x300x1.6mm Aluminum plate heat-sink.

# RATING AND CHARACTERISTIC CURVES (HBL4A THRU HBL4M)

FIG. 1 - MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG. 2 - TYPICAL FORWARD CURRENT DERATING CURVE




FIG. 3 - TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG. 4 - TYPICAL REVERSE CHARACTERISTICS

