



DC COMPONENTS CO., LTD.

RECTIFIER SPECIALISTS

1S2
THRU
1S10

TECHNICAL SPECIFICATIONS OF SCHOTTKY BARRIER RECTIFIER

VOLTAGE RANGE - 20 to 100 Volts


CURRENT - 1.0 Ampere

FEATURES

- * Low power loss, high efficiency
- * Low leakage
- * Low forward voltage
- * High current capability
- * High speed switching
- * High surge capability
- * High reliability

MECHANICAL DATA

- * Case: Molded plastic
- * Epoxy: UL 94V-0 rate flame retardant
- * Lead: MIL-STD-202E, Method 208 guaranteed
- * Polarity: Color band denotes cathode end
- * Mounting position: Any
- * Weight: 0.12 gram



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25 °C ambient temperature unless otherwise specified.
Single phase, half wave, 60 Hz, resistive or inductive load.
For capacitive load, derate current by 20%.

	SYMBOL	1S2	1S3	1S4	1S5	1S6	1S8	1S10	UNITS	
Maximum Recurrent Peak Reverse Voltage	V _{RRM}	20	30	40	50	60	80	100	Volts	
Maximum RMS Voltage	V _{RMS}	14	21	28	35	42	56	70	Volts	
Maximum DC Blocking Voltage	V _{DC}	20	30	40	50	60	80	100	Volts	
Maximum Average Forward Rectified Current .375"(9.5mm) lead length	I _O	1.0							Amps	
Peak Forward Surge Current 8.3 ms single half sine-wave superimposed on rated load (JEDEC Method)	I _{FSM}	35							Amps	
Maximum Instantaneous Forward Voltage at 1.0A DC	V _F	.55		.70		0.85			Volts	
Maximum DC Reverse Current at Rated DC Blocking Voltage	I _R	@T _A = 25°C	1.0							mAmps
		@T _A = 100°C	10							mAmps
Typical Thermal Resistance (Note 1)	R _{θJA}	50							°C/W	
Typical Junction Capacitance (Note 2)	C _J	110							pF	
Operating Temperature Range	T _J	-65 to + 150							°C	
Storage Temperature Range	T _{STG}	-65 to + 150							°C	

NOTES : 1. Thermal Resistance (Junction to Ambient): Vertical PC Board Mounting, 0.375"(9.5 mm) Lead Length.
2. Measured at 1 MHz and applied reverse voltage of 4.0 volts.

RATING AND CHARACTERISTIC CURVES (1S2 THRU 1S10)

FIG. 1 - TYPICAL FORWARD CURRENT DERATING CURVE




FIG. 2 - TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG. 3A - TYPICAL REVERSE CHARACTERISTICS




FIG. 3 - TYPICAL REVERSE CHARACTERISTICS




FIG. 4 - TYPICAL JUNCTION CAPACITANCE




FIG. 5 - MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT

