



**DC COMPONENTS CO., LTD.**

RECTIFIER SPECIALISTS

**SD820S  
THRU  
SD8100S**

**TECHNICAL SPECIFICATIONS OF SCHOTTKY BARRIER RECTIFIER**

**VOLTAGE RANGE - 20 to 100 Volts**

**CURRENT - 8.0 Amperes**

**FEATURES**

- \* Metal to silicon rectifier majority carrier conduction
- \* Low power loss, High efficiency
- \* High current capability
- \* Low forward voltage drop
- \* High surge capacity
- \* For use in low voltage high frequency inverters, free wheeling, and polarity protection applications

**MECHANICAL DATA**



- \* Case: Molded plastic
- \* Epoxy: UL 94V-0 rate flame retardant
- \* Terminals: Solder plated, solderable per MIL-STD-750, Method 2026
- \* Mounting position: Any
- \* Weight: 0.4 grams Approx.

**MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS**

Ratings at 25°C ambient temperature unless otherwise specified.  
Single phase, half wave, 60Hz, resistive or inductive load.  
For capacitive load, derate current by 20%.



TO-252(DPAK)



Dimensions in inches and (millimeters)

	SYMBOL	SD820S	SD830S	SD840S	SD850S	SD860S	SD880S	SD8100S	UNITS	
Maximum Recurrent Peak Reverse Voltage	V <sub>RRM</sub>	20	30	40	50	60	80	100	Volts	
Maximum RMS Voltage	V <sub>RMS</sub>	14	21	28	35	42	56	70	Volts	
Maximum DC Blocking Voltage	V <sub>DC</sub>	20	30	40	50	60	80	100	Volts	
Maximum Average Forward Rectified Current at T <sub>C</sub> =75°C	I <sub>O</sub>	8.0							Amps	
Peak Forward Surge Current 8.3 ms single half sine-wave superimposed on rated load (JEDEC Method)	I <sub>FSM</sub>	100							Amps	
Maximum Instantaneous Forward Voltage at 4.0A DC for "C suffixed", and at 8.0A DC for "Y suffixed" & "no suffix"	V <sub>F</sub>	0.65			0.75		0.85		Volts	
Maximum DC Reverse Current at Rated DC Blocking Voltage	I <sub>R</sub>	@ T <sub>A</sub> = 25°C	2.0							mAmps
		@ T <sub>A</sub> = 100°C	50							
Typical Thermal Resistance (Note1)	R <sub>θJA</sub>	80							°C/W	
Typical Junction Capacitance (Note 2)	C <sub>J</sub>	700							pF	
Storage Operating Temperature Range	T <sub>J</sub> , T <sub>STG</sub>	-55 to + 125							°C	

Note : 1. Mounted on PC Board with 14mm<sup>2</sup>(0.013mm thick) copper pad areas.

2. Measured at 1 MHz and applied reverse voltage of 4.0 volts.

# RATING AND CHARACTERISTIC CURVES (SD820S THRU SD8100S)

FIG. 1 - TYPICAL FORWARD CURRENT DERATING CURVE




FIG. 2 - TYPICAL REVERSE CHARACTERISTICS




FIG. 3 - TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG. 4 - TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG. 5 - TYPICAL JUNCTION CAPACITANCE





FIG. 6 - MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT



## Disclaimer

Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold *DC COMPONENTS* harmless against all damages.

*DC COMPONENTS* disclaims any and all liability arising out of the application or use of any product, including consequential or incidental damages. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application.

*DC COMPONENTS* reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein, and disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Unless otherwise in writing, *DC COMPONENTS* products are intended for use as general electronic components in standard applications ( eg: Consumer electronic, Computer equipment, Office equipment, etc.), and not recommended for use in a high specific application where a failure or malfunction of the device could result in human injury or death ( eg: Aerospace equipment, Submarine cables, Combustion equipment, Safety devices, Life support systems, etc.)

Customers using or selling *DC COMPONENTS* products not expressly indicated for use in such applications do so at their own risk. If customer intended to use *DC COMPONENTS* standard quality grade devices for applications not envisioned by *DC COMPONENTS*, please contact our sales representatives in advance.



*DC COMPONENTS CO., LTD.*